






# iHD322 POE Smart Camera



## Features

-  Biometric Capture
-  Tracking
-  Filtering
-  Vivid HD Image
-  Simple Setup

| Description     | Part Number  |
|-----------------|--------------|
| Ceiling Adaptor | TR-UM06-E-IN |
| Wall Mount      | TR-WM03-C-IN |
| Power Supply    | GS-PWR-1A    |

## Specification

|                           |                       |  |                   |
|---------------------------|-----------------------|--|-------------------|
| <b>Image</b>              | AI Chip               | Movidius   |                   |
|                           | Resolution            | 1920 x 1080  |                   |
|                           | Shutter               | 1/25 s ~ 1/10000 s - auto adjust   |                   |
|                           | Min Illumination      | Color: 0.001 Lux @ F1.6;<br>Black & White: 0.00001 Lux @ F1.6                          |                   |
|                           | Optical Zoom          | 4.0 mm   |                   |
| <b>Video</b>              | Compression           | Ultra 265/H.264/MJPEG  |                   |
|                           | Streams               | Main stream  | 1080P(1920×1080)  |
|                           |                       | Sub streams  | D1(720×576)/1080P |
|                           | Max Frame Rate        | 30 fps   |                   |
|                           | Bit Rate              | 32 Kbps ~16 Mbps   |                   |
| <b>Object Detection</b>   | Feature Analysis      | Face capture, tracking and filtering   |                   |
|                           | Image Format          | JPEG encoding  |                   |
| <b>Network</b>            | Interface             | RJ45 - 10/100 Ethernet   |                   |
|                           | Protocol              | IPv4, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP |                   |
|                           | Access Standard       | ONVIF  |                   |
|                           | Users                 | Up to 6 simultaneously   |                   |
| <b>General Parameters</b> | Housing               | White aluminum   |                   |
|                           | Power Supply          | DC 12 V 1 A or POE 802.3af   |                   |
|                           | Operating Environment | -35°C~60°C, 95% RH (non-condensing)  |                   |
|                           | Size (mm)             | 108 D x 81   |                   |
|                           | Weight (g)            | 450  |                   |