






iHD323 POE Smart Camera



Features

-  Biometric Capture
-  Tracking
-  Filtering
-  Vivid HD Image
-  Simple Setup

Description	Part Number
Ceiling Adaptor	TR-UM06-E-IN
Wall Mount	TR-WM03-C-IN
Power Supply	GS-PWR-1A

Specification

Image	AI Chip	Movidius	
	Resolution	1920 x 1080	
	Shutter	1/25 s ~ 1/10000 s - auto adjust	
	Min Illumination	Color: 0.0005 Lux @ F1.2; Black & White: 0.00001 Lux @ F1.2	
	Optical Zoom	2.7 mm - 13.5 mm	
Video	Compression	Ultra 265/H.264/MJPEG	
	Streams	Main stream	1080P(1920×1080)
		Sub streams	D1(720×576)/1080P
	Max Frame Rate	30 fps	
	Bit Rate	32 Kbps ~16 Mbps	
Object Detection	Feature Analysis	Face capture, tracking and filtering	
	Image Format	JPEG encoding	
Network	Interface	RJ45 - 10/100 Ethernet	
	Protocol	IPv4, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP	
	Access Standard	ONVIF	
	Users	Up to 6 simultaneously	
	General Parameters	Housing	White aluminum
	Power Supply	DC 12 V 1 A or POE 802.3af	
	Operating Environment	-35°C~60°C, 95% RH (non-condensing)	
	Size (mm)	148 D x 111.3	
	Weight (g)	920	