

Fever Access Control Terminal



The pdActive access control terminal with digital temperature measurement provides non-contact temperature detection in a rugged terminal that can be deployed at doors, gates, turnstiles, kiosks or stand-alone. The terminal supports rapid body temperature detection with audible and electronic alarms for temperature, mask and access deny.

Ordering Information

Model	Comment
i-ACT-TEMP	Fever Access Control Terminal

Features

- Non-contact abnormal body temperature warnings and triggers
- Mask detection
- Configurable temperature detection threshold
- Recognition time 0.2 seconds
- WDR, 2MP (1080P) low illumination wide-angle ONVIF camera captures high quality images in complex lighting scenes
- Anti-spoofing detection (human liveness)
- Screen sleep with minimum brightness to prevent glare
- Tamper protection, open door timeout, and door open with fire alarms

Product Specification

Features Parameter	Description
Operation System	Linux
Storage Capacity	4GB
Measurement Range	90°F - 110°F
Measurement Accuracy	0.2°F
Measurement Deviation	±0.2°F
Measurement Distance	3 ft
Authentication Modes	Body temperature
Network	10/100 Ethernet
Record Management	Local recording and real-time upload
Interface	LAN, RS485, Alarm Input, Alarm Output, Lock, Door Contact, Exit Button
Power Supply	12 V DC
Screen	7 inch 600×1024
Camera	Dual Lens 1080P
Supplement Light	Soft LED and infrared
Size	134.0mm x 33.0mm x 305.0mm
Environment	(-20°C~+65°C, 95% RH non-condensing)
Protection Level	IP 54

**Product specifications and availability are subject to change without notice.*

Fever Access Control Terminal

