

# Fever Access Control Terminal



The pdActive access control terminal with digital temperature measurement provides non-contact temperature detection in a rugged terminal that can be deployed at doors, gates, turnstiles, kiosks or stand-alone. The terminal supports rapid body temperature detection with audible and electronic alerts for temperature, mask and access deny.

## Ordering Information

Model	Comment
i-ACT-TEMP-P/W	Fever Access Control Terminal
i-ACT-PED	Floor Mount

\*P=Pedestal, W=Wall

## Features

- Non-contact abnormal body temperature warnings and triggers
- Mask detection
- Configurable temperature detection threshold
- Recognition time 0.2 seconds
- WDR, low illumination, wide-angle camera captures high quality images in complex lighting scenes
- Anti-spoofing detection (human liveness)
- Screen sleep with minimum brightness to prevent glare

## Product Specification

Features Parameter	Description
Operation System	Linux
Measurement Range	90°F - 110°F
Measurement Accuracy	0.5°F
Measurement Deviation	±0.2°F
Measurement Distance	3 ft
Network	10/100 Ethernet
Record Management	Real-time upload
Interface	LAN, RS232, Alarm Input, Alarm Output, Lock, Door Contact, Exit Button
Power Supply	12 V DC
Screen	8 inch 600×1024
Camera	Dual Lens 1080P
Supplement Light	Soft LED and Infrared
Size	144.0mm x 25.0mm x 273.0mm
Environment	(-20°C~+65°C, 95% RH non-condensing)
Protection Level	IP 54
Mount	Pedestal, Wall

\*Product specifications and availability are subject to change without notice.

# Fever Access Control Terminal

Location Name: 
 End Date: 
 Start Date: 
 Access: 
 Compliance:

Show  entries

Search:

Zone	Name	Live Image	File Image	Group	Time	Temperature	
EntryTemp	Sally			Staff/Contractors	2020-07-29 18:17:09	96.3	
EntryTemp	Brenda			Staff/Contractors	2020-07-29 18:16:16	99.5	
EntryTemp				Staff/Contractors	2020-07-27 08:47:30	97.5	

