pdActive

Fever Access Control Terminal





The pdActive access control terminal with digital temperature measurement provides non-contact temperature detection in a rugged terminal that can be deployed at doors, gates, turnstiles, kiosks or stand-alone. The terminal supports rapid body temperature detection with audible and electronic alerts for temperature, mask and access deny.

| Ordering Information | |
|----------------------|-------------------------------|
| Model | Comment |
| i-ACT-TEMP-P/W | Fever Access Control Terminal |
| i-ACT-PED | Floor Pedestal |

*P=Pedestal, W=Wall

Features

- Non-contact abnormal body temperature warnings and triggers
- Mask detection
- Configurable temperature detection threshold
- Recognition time 0.2 seconds
- WDR, low illumination, wide-angle camera captures high quality images in complex lighting scenes
- Anti-spoofing detection (human liveness)
- Screen sleep with minimum brightness to prevent glare

| Product Specification | |
|-----------------------|---------------------------------------------------------------------------|
| Features Parameter | Description |
| Operation System | Linux |
| Measurement Range | 90°F - 110°F |
| Measurement Accuracy | 0.5°F |
| Measurement Deviation | ±0.2°F |
| Measurement Distance | 3 ft |
| Network | 10/100 Ethernet |
| Record Management | Real-time upload |
| Interface | LAN, RS232, Alarm Input, Alarm Output, Lock, Door Contact, Exit Button |
| Power Supply | 12 V DC |
| Screen | 8 inch 600×1024 |
| Camera | Dual Lens 1080P |
| Supplement Light | Soft LED and Infrared |
| Size | 144.0mm x 25.0mm x 273.0mm |
| Environment | (-20°C~+65°C, 95% RH non-condensing) |
| Protection Level | IP 54 |
| Mount | Pedestal, Wall |

^{*}Product specifications and availability are subject to change without notice.

Fever Access Control Terminal







